



**H E N A N
F O I L S**

FOIL MANUFACTURER & SUPPLIER

**THE WIDEST CHOICE FOR THE FINEST
STAMPING FOILS & LAMINATE FILMS**

TECHNICAL DATA SHEET

TF SERIES - HOT STAMPING FOIL (DIGITAL PRINTING)

INTRODUCTION

✓ Toner foil is a process where foil is bonded to a toner image area that was created using either a laser printer or a copy machine.

APPLICATIONS INCLUDE

- ✓ Unprinted
- ✓ printed papers or paperboard
- ✓ unprinted paper like Byelaya paper
- ✓ Chip board paper
- ✓ Single gummed paper
- ✓ Two-side offset paper
- ✓ Art paper

PROPERTIES OVERVIEW

- ✓ Excellent stamping effect
- ✓ Excellent resistance to water
- ✓ Offers very good Performance for large area print and detailed work
- ✓ Nontoxic

MACHINE DETAILS:

- ✓ Excellent gloss
- ✓ Good coverage
- ✓ Clean stamping
- ✓ Easy release
- ✓ High abrasion resistance
- ✓ High processing speed
- ✓ Temperature : 110~ 160centi grade

STORAGE:

- ✓ Digital foils should be stored in a dry, cool place away from direct sunlight. The recommended storage temperature is between 15°C to 25°C.
- ✓ The foils should be stored in their original packaging to protect them from dust, dirt, and other contaminants. Digital foils should be handled with care to avoid creasing or damage to the foil surface.

ATTENTION : THE ABOVE INFORMATION IS A GUIDELINE ONLY; CUSTOMER SHALL ADJUST THE PARAMETERS ACCORDING TO DIFFERENT MACHINE AND CHECK WITH FINAL EFFECT

SAFETY AND HANDLING

- ✓ Digital foils are safe to handle and do not pose any significant health risks. However, it is recommended to wear gloves while handling the foils to avoid any possible irritation from contact with the adhesive or foil surface.

DISCLAIMER

- ✓ This information is based on our current knowledge and experience, and is provided as a guide to the use of our product. It is the responsibility of the user to test the product for its intended application and determine its suitability for the specific use.
- ✓ We do not accept any liability for damage or loss resulting from the use of our product.

AVAILABILITY

- ✓ 13 / 15 days.

Contact Henan Foils for availability of other shades.

The information contained in this data sheet is believed to be reliable, but the suitability of the products must be judged by the individual user. These specifications may be subject to change without notification or obligation. No warranty or liability for results obtained is expressed or implied.

FOIL SHOWCASE



**For more information,
Please Contact Us!**

INTERNATIONAL OFFICE

Bahia Grande
C/ Magallanes 37B,
07609 Lluçmajor | Mallorca | Spain
M. +34 616 699 909
T. Int. +34 971 237 430
info@henanfoils.net

ASIA

T.+86 150 6780 6619
henanfoils@henanfoils.net

SOUTH AMERICA

ARGENTINA
Carlos y Emmanuel Brito Serpap
Moreno 6715 - 2° D
B1625FRK Belen de Escobar - Buenos Aires - ARGENTINA
T. +541143429583 | CUIT 20-25597755-6
argentina@henanfoils.net